



# CHEMRAZ® 605

## SEALING SOLUTIONS

Chemraz® 605 is ideally suited for challenging fluid handling applications. A high-temperature compound with superior compression set resistance, physical properties and excellent chemical resistance, it excels in demanding static and semi-dynamic applications. Chemraz 605 exhibits unparalleled performance with hot amines, steam and water and functions well in temperatures ranging from 0°F to 500°F (-18°C to 260°C).

Available in O-rings, gaskets and many other custom shapes, Chemraz 605 possesses a broad chemical resistance range. The 605 compound is suitable for use in a wide variety of media including acids, caustics, aldehydes, esters, ethers, aromatics, hot water, steam, amines, methanol, ketones, TBA and MTBE.



## FEATURES & BENEFITS

- High-temperature capability
- Excellent compression set resistance
- Broad chemical compatibility for use with a wide range of harsh solutions
- Excellent in amines, hot water and steam
- NAMS A USP Class VI Certified

## AVAILABILITY

- Mechanical seals
- Medical devices
- Pump housings
- Diagnostic equipment
- Reactors
- Sampling/metering equipment
- Mixers
- Bearing isolators
- Compressors
- Controls/instrumentation
- Valves
- Sprayers/dispensers

## Contact Us

Greene, Tweed  
Fluid Handling  
Houston, TX, USA

Tel: +1.281.821.2094  
Tel: +1.800.820.9005  
Fax: +1.281.821.2696

www.gtweed.com

## TYPICAL PROPERTIES\*

Physical Properties	ASTM Method	Typical Value
Color		Black
Specific Gravity	D297	1.97
Hardness, Shore A, Points	D2240	80
Elongation @ Break, %	D1414	130
Tensile Modulus, psi (MPa)		
Modulus @ 50% Elongation	D1414	420 (2.9)
Modulus @ 100% Elongation	D1414	1310 (9.0)
Tensile Strength @ Break, psi (MPa)	D1414	2150 (14.8)

\* Note: Unless otherwise indicated, all tests are performed on (-214) O-rings.